



INDUSTRIAL TIRES





TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



S850

Brand	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single (KG)	Dual (KG)	A.P. (KPA)	A.P. (PSI)
SAILUN	7.00R16	118/114L	14	10.5	5.50F	775	200	14.25	1320	1180	770	112
SAILUN	7.50R16	125/121K	16	12.5	6.00G	805	215	14.76	1650	1450	870	126
SAILUN	7.50R16	129/128K	18	12.5	6.00G	805	215	14.76	1850	1800	900	130
SAILUN	8.25R16	132/128K	18	14	6.50H	865	235	15.63	2000	1800	870	126
SAILUN	10.00R20	149/146K	18	15.2	7.5	1054	278	19.13	3250	3000	930	135



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



S750

Brand	Size	L.I. /S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single (KG)	Dual (KG)	A.P. (KPA)	A.P. (PSI)
SAILUN	8.25R16	132/128K	18	15.5	6.50H	865	235	15.63	2000	1800	870	126
SAILUN	10.00R20	149/146K	18	18	7.5	1054	278	19.13	3250	3000	930	135



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SFR39

Brand	Size	L.I./S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single (KG)	Dual (KG)	A.P. (KPA)	A.P. (PSI)
SAILUN	7.50R16	129/128K	18	11.5	6.00G	805	215	14.76	1850	1800	900	130
SAILUN	8.25R16	132/128K	18	12.5	6.50H	865	235	15.63	2000	1800	870	126



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



S696

Brand	Size	L.I./S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single (KG)	Dual (KG)	A.P. (KPA)	A.P. (PSI)
SAILUN	6.50R16	110/105M	12	10.5	5.50F	750	185	13.78	1060	925	670	97
SAILUN	7.00R16	115/110M	12	11.5	5.50F	775	200	14.25	1215	1060	670	97
SAILUN	7.00R16	118/114L	14	11.5	5.50F	775	200	14.25	1320	1180	770	112
SAILUN	7.50R16	122/118K	14	12.5	6.00G	805	215	14.76	1500	1320	770	112
SAILUN	7.50R16	125/121K	16	12.5	6.00G	805	215	14.76	1650	1450	870	126
SAILUN	7.50R20	130/128L	14	13.5	6.0	935	215	17.13	1900	1800	830	120
SAILUN	8.25R16	128/124L	16	13.5	6.50H	855	235	15.63	1800	1600	770	112



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SAR16

Brand	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single (KG)	Dual (KG)	A.P. (KPA)	A.P. (PSI)
SAILUN	7.00R16	118/114L	14	11.0	5.50F	775	200	14.25	1320	1180	770	112



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SAR19

Brand	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single (KG)	Dual (KG)	A.P. (KPA)	A.P. (PSI)
SAILUN	195/85R16	118/114L	14	10	5 1/2J	738	196	14.06	1320	1180	750	109
SAILUN	225/90R17.5	130/128L	14	13.5	6.75	851	226	15.47	1900	1800	760	110



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



S637/S637+

Brand	Size	L.I./S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single (KG)	Dual (KG)	A.P. (KPA)	A.P. (PSI)
SAILUN	9.5R17.5	129/127M	14PR	13.5	6.75	842	240	15.63	1850	1750	750	110
SAILUN	9.5R17.5	132/130M	16PR	13.5	6.75	842	240	15.63	2000	1900	830	120
SAILUN	9.5R17.5	143/141J	18PR	13.5	6.75	842	240	15.63	2725	2575	875	125
SAILUN	9R22.5	136/134M	14PR	13.5	6.75	974	229	17.99	2240	2120	830	120
SAILUN	10R22.5	141/139M	14PR	14.5	7.50	1019	254	18.74	2575	2430	790	115



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



S711

Brand	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single (KG)	Dual (KG)	A.P. (KPA)	A.P. (PSI)
SAILUN	7.05R16	122/118L	14	14.5	6.00G	815	215	14.76	1500	1320	770	112
SAILUN	8.25R16	128/124K	16	15.5	6.50H	865	235	15.63	1800	1600	770	112
SAILUN	8.25R20	139/137K	16	16.5	6.5	986	236	17.80	2430	2300	930	135
SAILUN	9.00R20	144/142K	16	17.0	7.0	1030	259	18.54	2800	2650	900	130
SAILUN	9.00R20	146/144J	18	17.0	7.0	1030	259	18.54	3000	2800	970	140
SAILUN	10.00R20	149/146K	18	17.0	7.5	1065	278	19.13	3250	3000	930	135



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



S812

Brand	Size	L.I./S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single (KG)	Dual (KG)	A.P. (KPA)	A.P. (PSI)
SAILUN	6.50R16	110/105M	12	10.5	5.50F	750	185	13.78	1060	925	670	97
SAILUN	7.00R16	118/114K	14	11.5	5.50F	775	200	14.25	1320	1180	770	112
SAILUN	7.50R16	122/118K	14	12.5	6.00G	805	215	14.76	1500	1320	770	112
SAILUN	8.25R16	126/122K	14	13.5	6.50H	855	235	15.63	1700	1500	670	97
SAILUN	8.25R16	128/124K	16	13.5	6.50H	855	235	15.63	1800	1600	770	112



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



S828

Brand	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single (KG)	Dual (KG)	A.P. (KPA)	A.P. (PSI)
SAILUN	7.00R16	118/114K	14	11.5	5.50F	775	200	14.25	1320	1180	770	112
SAILUN	7.50R16	122/118K	14	12.5	6.00G	805	215	14.76	1500	1320	770	112
SAILUN	8.25R16	128/124L	16	13.5	6.50H	855	235	15.63	1800	1600	770	112
SAILUN	8.25R20	139/137K	16	13.5	6.5	974	236	17.80	2430	2300	930	135
SAILUN	9.00R20	144/142K	16	16.0	7.0	1019	259	18.54	2800	2650	900	130
SAILUN	10.00R20	149/146K	18	16.0	7.5	1054	278	19.13	3250	3000	930	135



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



S889

Brand	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single (KG)	Dual (KG)	A.P. (KPA)	A.P. (PSI)
SAILUN	9.00R20	144/142K	16	15.5	7.0	1019	259	18.54	2800	2650	900	130
SAILUN	10.00R20	149/146K	18	16.5	7.5	1054	278	19.13	3250	3000	930	135



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



S917

Brand	Size	L.I./S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single (KG)	Dual (KG)	A.P. (KPA)	A.P. (PSI)
SAILUN	7.50R16	122/118G	14	14.5	6.00G	815	215	14.76	1500	1320	770	112
SAILUN	8.25R16	128/124G	16	15.5	6.50H	865	235	15.63	1800	1600	770	112



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



S918

Brand	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single (KG)	Dual (KG)	A.P. (KPA)	A.P. (PSI)
SAILUN	7.00R16	118/114G	14	13.5	5.50F	785	200	14.25	1320	1180	770	112
SAILUN	7.50R16	122/118G	14	14.5	6.00G	815	215	14.76	1500	1320	770	112
SAILUN	8.25R20	139/137G	16	17.0	6.5	986	236	17.80	2430	2300	930	135
SAILUN	9.00R20	144/142F	16	20.5	7.0	1030	259	18.54	2800	2650	900	130



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



AP886

Brand	Size	Standard Rim(inch)	PR	Load				Pressure				Load Index		Tread Depth (mm)	Speed Grade	Inflated Tire Dimension(mm)	
				Kg		Lbs		Kpa		Psi							
				S	D	S	D	S	D	S	D	S	D				
ROADX	7.00R16	5.5F	14	1320	1180	2910	2600	770	770	112	112	118	114	10.5	J	775	200
ROADX	7.50R16	6.0G	16	1650	1450	3640	3195	870	870	126	126	125	121	12.5	J	805	215
ROADX	7.50R16	6.0G	18	1850	1800	4080	3970	900	900	130	130	129	128	12.5	J	805	215
ROADX	8.25R16	6.50H	18	2000	1800	4410	3970	870	870	126	126	132	128	14	J	865	235
ROADX	10.00R20	7.5	18	3250	3000	7160	6610	930	930	135	135	149	146	15.2	K	1054	278



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



RH183

Brand	Size	Standard Rim(inch)	PR	Load				Pressure				Load Index		Tread Depth (mm)	Speed Grade	Inflated Tire Dimention(mm)	
				Kg		Lbs		Kpa		Psi							
				S	D	S	D	S	D	S	D	S	D				
ROADX	7.50R16	6.00G	16	1650	1450	3640	3195	870	870	126	126	125	121	11.5	J	805	215
ROADX	7.50R16	6.00G	18	1850	1800	4080	3970	900	900	130	130	129	128	11.5	J	805	215
ROADX	8.25R16	6.05H	18	2000	1800	4410	3970	870	870	126	126	132	128	12.5	J	865	235



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



RH300

Brand	Size	Standard Rim(inch)	PR	Load				Pressure				Load Index		Tread Depth (mm)	Speed Grade	Inflated Tire Dimension(mm)	
				Kg		Lbs		Kpa		Psi						D	B
				S	D	S	D	S	D	S	D	S	D				
ROADX	6.50R16	5.50F	12	1060	925	2335	2040	670	670	97	97	110	105	10.5	L	750	185
ROADX	7.00R16	5.50F	14	1320	1180	2910	2600	770	770	112	112	118	114	11.5	N	775	200
ROADX	7.50R16	6.00G	14	1500	3120	3305	2910	770	770	112	112	122	118	12.5	L	805	215
ROADX	7.50R16	6.00G	16	1650	1450	3640	3195	870	870	126	126	125	121	14.5	K	805	215
ROADX	8.25R16	6.50H	16	1800	1600	3970	3525	770	770	112	112	128	124	14	L	865	235



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



AP865

Brand	Size	Standard Rim(inch)	PR	Load				Pressure				Load Index		Tread Depth (mm)	Speed Grade	Inflated Tire Dimation(mm)	
				Kg		Lbs		Kpa		Psi						D	B
				S	D	S	D	S	D	S	D						
ROADX	7.50R16	6.00G	14	1500	1320	3305	2910	770	770	112	112	122	118	12.5	L	805	215
ROADX	8.25R16	6.50H	16	1800	1600	3970	3525	770	770	112	112	128	124	14	L	865	235
ROADX	8.25R20	6.50H	16	2430	2300	5355	5070	930	930	135	135	139	137	13	K	974	236
ROADX	9.00R20	7.0	16	2800	2650	6175	5840	900	900	130	130	144	142	15	K	1019	259
ROADX	9.00R20	7.0	14	2575	2430	5675	5355	790	790	115	115	141	139	15	K	1019	259
ROADX	10.00R20	7.5	18	3250	3000	7160	6610	930	930	135	135	149	146	16	K	1054	278


TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS


MS668

Brand	Size	Standard Rim(inch)	PR	Load				Pressure				Load Index		Tread Depth (mm)	Speed Grade	Inflated Tire Dimention(mm)	
				Kg		Lbs		Kpa		Psi						D	B
				S	D	S	D	S	D	S	D	S	D				
ROADX	7.00R16	5.50F	14	1320	1180	2910	2600	770	770	112	112	118	114	13.5	K	775	200
ROADX	7.50R16	6.00G	14	1500	1320	3305	2910	770	770	112	112	122	118	12.5	L	805	215
ROADX	8.25R16	6.50H	16	1800	1600	3970	3525	770	770	112	112	128	124	14	L	865	235
ROADX	8.25R20	6.50H	16	2430	2300	5355	5070	930	930	135	135	139	137	13	K	974	236
ROADX	9.00R20	7.0	16	2800	2650	6175	5840	900	900	130	130	144	142	15	K	1019	259
ROADX	10.00R20	7.5	18	3250	3000	7160	6610	930	930	135	135	149	146	16	K	1054	278



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



DT992

Brand	Size	Standard Rim(inch)	PR	Load				Pressure				Load Index		Tread Depth (mm)	Speed Grade	Inflated Tire Dimation(mm)	
				Kg		Lbs		Kpa		Psi							
				S	D	S	D	S	D	S	D	S	D				
ROADX	7.50R16	6.00G	14	1500	1320	3310	2910	770	770	112	112	122	118	15.5	L	805	215
ROADX	8.25R16	6.50H	16	1800	1600	3970	3530	770	770	112	112	128	124	15.5	L	865	235
ROADX	9.5R17.5	6.75	18	2725	2575	6005	5675	875	875	125	125	143	141	17	K	842	240
ROADX	8.25R20	6.5	16	2430	2300	5360	5070	930	930	135	135	139	137	17	K	974	236
ROADX	9.00R20	7.0	16	2800	2650	6170	5840	900	900	130	130	144	142	18	K	1019	259
ROADX	10.00R20	7.5	18	3250	3000	7160	6610	930	930	135	135	149	146	19	K	1054	278